

# Scanners that stand up to the challenge

### High-impact advantages for low-volume production scanning

Documents aren't always the perfect size, shape or quality for scanning. Which is exactly why the Kodak i1420 and i1440 Scanners are perfect for scanning all your documents.

Our tabletop Scanners easily handle everything from small cards to very long printouts. And they provide the competitive edge your business needs with speeds up to 75 ppm/150 ipm, enhanced Perfect Page image quality, great ease of use and awesome productivity.

# Handles virtually all document types, sizes and shapes

- Scan documents up to 863 mm long and everything from onionskin to card stock
- Optional Plug&Play A3 and A4 "tethered" flatbeds for convenient scanning of bound materials

# Enhanced image quality with the latest Perfect Page imaging

• Automatic colour detection – based on document content, automatically outputs images in colour, greyscale or black-and-white

- Background colour smoothing removes variations in background colour
- Improved colour accuracy enhances images for truer, more consistent colours
- Interactive colour output adjustment adjust brightness, contrast and colour balance to personal preference
- Automatic orientation based on document content, automatically orients the scanned image correctly for reading

### Functions of the premium model i1440

- Long document mode scans documents up to 6.1 m and beyond!
- Special document mode autofeeds even irregularly shaped documents
- Photo extraction automatically locates, extracts and outputs a photo as a separate image file
- Trainable electronic colour dropout "learns" up to three background colours to drop out
- Segmented black-and-white output optimises the image quality of text and photo regions independently, allowing photos to be rendered with more detail and clarity
- Toggle patch automatically switches between black-and-white and colour scanning "on the fly"

### "Ease of Use" couldn't be easier

- Smart touch feature allows you to scan to file, e-mail, desktop applications or SharePoint with just one click
- Bundled with Kodak Capture Desktop Software for simple batch scanning.
  With an upgrade path to professional level Kodak Capture Pro Software with Indexing, Barcode and OCR reading
- USB 2.0 interface provides easy connectivity and fast image transfer
- Post-scan document imprinter prints tracking information directly on documents with full speed

#### Kodak Service & Support

You can upgrade the standard one year warranty with a three Year PerformancePlus service contract, which is designed to meet your specific business needs. It helps protect your productivity, avoids unexpected charges and, keeps your scanner performing optimally while protecting your business processes.

#### Kodak i1420 and i1440 Scanners

Recommended Daily Volume	i1420: up to 12,000 pages per day; i1440: up to 15,000 pages per day
Throughput Speeds (200 dpi landscape, letter-size, black-and-white/greyscale/colour)	i1420: up to 60 ppm/120 ipm; i1440: up to 75 ppm/150 ipm (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC)
Scanning Technology	i1420/i1440: dual CCD; Greyscale output bit depth is 256 levels (8-bit); Colour capture bit depth is 48 bits (16 x 3); Colour output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi and optional A3 and A4 flatbed accessories; 1200 dpi (A4 flatbed accessory)
Illumination	Dual fluorescent (cold cathode)
Output Resolution	75, 100, 150, 200, 240, 300, 400, 600 and 1200 dpi
Maximum Document Size	297 mm x 863 mm ; for i1440, on long document mode: 254 mm x 6.1 m
Minimum Document Size	64 mm x 89 mm
Paper Thickness and Weight	34-413 g/m <sup>2</sup> paper
Feeder	Up to 150 sheets of 60 g/m <sup>2</sup> paper
Multi-feed Detection	With 3D ultrasonic technology
Connectivity	USB 2.0, 2m USB cable included
Bundled Software	TWAIN, ISIS, SANE and Windows Imaging Architecture Drivers; Kodak Capture Desktop Software, and Smart Touch
Imaging Features (in the scanner)	Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autocrop; relative cropping; aggressive cropping; electronic colour dropout; dual-stream scanning; interactive colour, brightness and contrast adjustment; automatic orientation; automatic colour detection; background colour smoothing i1440 only: segmented black-and-white images, automatic photo cropping, multiple electronic colour dropout, trainable electronic colour
5W 5	dropout, long document mode, special document mode, toggle patch
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, PDF, searchable PDF
Imprinting	Post-scan document imprinter***
Accessories	Kodak A3 Flatbed (black background) Accessory with 1.8-meter cable, Kodak A4 Flatbed (white background) Accessory with 1.8-meter cable; Optional A4 black imaging background accessory
Electrical Requirements	100-240 V (International); 50/60 Hz; universal power supply included
Power Consumption	Scanner: Power Off mode: <1 Watt; Sleep mode: <4 Watts; Running: <60 Watts Scanner with A3 Flatbed: Sleep mode: <6 Watts; Running: <70 Watts Scanner with A4 Flatbed: Sleep mode: <6 Watts; Running: <63 Watts
Environmental Factors	Energy Star qualified scanners; Operating temperature: 15-35° C Operating humidity: 15-76 percent relative humidity
Acoustical Noise (operator position sound pressure level)	Standby mode: <32 dB(A) Operating mode: <65 dB(A)
Recommended PC Configuration	For documents up to 356 mm long at 400 dpi: Pentium 4, 3.2 GHz processor, 512 MB RAM For documents up to 660 mm long at 400 dpi: Pentium 4, 3.2 GHz processor, 1 GB RAM For longer documents/higher resolutions: Pentium 4, 3.2 GHz processor, 3 GB RAM
Supported Operating Systems	Windows XP SP2 (32-bit ), Windows XP x64 Edition SP2; Windows 2000 Professional SP4, Windows Vista SP1 (32-bit and 64-bit), Windows 7 (32-bit and 64-bit), Windows 2003 Server x64 Edition, Linux Ubuntu 8.04, Fedora 9, and SUSE 11
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950 (C TUV Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-2 Harmonics, EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 Class B, VCCI (Class B), CNS 13438 (Class B), (BSMI Mark), UL 60950 (TUV US Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed module, separation module, feed rollers, roller cleaning pads, Staticide Wipes, image guides, pre-separation pad, inkjet cartridge holder, inkjet cartridges, ink blotters
Dimensions	Weight: 10.4 kg; Depth: 30 cm not including input tray and output tray; Width: 54.7 cm; Height: 36.5 cm
Warranty*	12 months on-site, 3-4 business days response time
Warranty Enhancement*	36 months PerformancePlus on-site, 8hrs response time, consumables included**

Specifications are subject to change without notice. \*There may be geographical limitations to the availability of Services. For full details please contact your Reseller of Kodak products or your local Kodak Service & Support organisation. \*\* Please see terms & conditions for PerformancePlus. \*\*\* Ink cartridge and ink cartridge holder must be purchased separately.

To learn more: www.kodak.com/go/i1400







Kodak







It's time for you AND Kodak

Printed using Kodak Technologies.

United Kingdom, Phone: +44 870 8502351, Fax: +44 870 850 2352 Nordic, Phone: +46 (8) 555 638 31, Fax: +46 (8) 555 995 04 Africa, Phone: +44 1442 846547, Fax: +44 1442 846606 Germany, Austria and Switzerland, Phone: +49 711 406 2535, Fax: +49 711 406 3619 Eastern Europe, Near and Middle East, Phone: +36 1 454 3031, Fax: +36 1 387 9113 France, Spain and Portugal, Phone: +33140013180, Fax +33140013981 Italy, Phone: +39 0266028338, Fax: +39 0266028358 The Netherlands, Phone: +31 33 2998751, Fax: +31 20 6545227 Belgium and Luxembourg, Phone: +32 2 352 27 04, Fax: +32 2 352 30 28

 $\ensuremath{\mathbb{C}}\xspace{\ensuremath{\mathsf{Kodak}}\xspace}$  , 2010. Kodak is a trademark of Kodak. Dolde Medien 45\_10

Subject to technical change without notice. CAT No. E-DI.007.0210.en.01